

Extruded Polystyrene Insulation **FOAMULAR**[®]



“Owens Corning’s Foamular insulation is an extruded polystyrene rigid foam insulation with stable, high insulating values and superior moisture resistance when compared to other types of foam insulation.”

Owens Corning has been producing insulation since 1935 and has been a leading force in the way the insulation industry has developed. Owens Corning is a member of EPA Climate leaders program, and is committed to reducing Greenhouse gas Emissions in the manufacturing process and through product performance.

“Insulation Is One Of The Most Effective Ways To Improve A Buildings Energy Efficiency.”



Austech has been nationally distributing building products for 25 years, and distributes Foamular Australia wide. Austech’s sales and technical team can recommend the best product for your application and help with the specification process.

New South Wales

Austech External Building Products
80 Tattersall Road, Blacktown NSW 2148
PO Box 4208 Marayong NSW 2148
Phone: 02 9831 1623
Fax: 02 9831 5043
Contact: Tony Curran
Email: sales@austech.com.au

Queensland

Austech External Building Products (QLD)
1/1089 Kingsford Smith Drive,
Eagle Farm Brisbane QLD 4009
Phone: 07 3268 3066
Fax: 07 3268 3021
Contact: Matt Reeder & Scott Follent
Email: sales@austech-qld.com.au

Victoria and South Australia

Austech External Building Products (VIC)
36 Isabella Street, Moorabbin VIC 3189
Phone: 03 9532 0131
Fax: 03 9532 1868
Contact: Alan Mooney
Email: sales-vic@austech.com.au

Western Australia

Austech External Building Products (WA)
20 Hilltop Ct, Mahogany Creek WA 6072
Phone: 08 9295 0500
Fax: 08 9295 6699
Contact: John Vadala
Email: sales-wa@austech.com.au

Tasmania

Austech External Building Products (TAS)
4/8 Melrose Court, Sandy Bay Hobart TAS 7005
Phone/Fax: 03 6225 4003
Contact: Tony Caldwell
Email: sales-tas@austech.com.au

New Zealand

Contact: Tony Curran
Email: sales-nz@austech.com.au

Application: Model Making

The Closed cell structure of Foamular combined with its high density and compressive strength ensure fine detail and finish can be achieved for most types of model making. Landscaping, diorama and structural componentry are amongst the long list of possibilities.



Material Sizes:

- Standard Sheet size – 2450 x 600

Thickness Available:

- 25, 30, 40, 50, 75 & 100 mm

Adhesive used with Foamular must be Polystyrene compatible (no solvent content)

Paints must be acrylic not solvent or oil based

If in doubt do a small test piece to check compatibility



For Technical Information, Contact Mike Nagle - 0417 268 660
mnagle@austech.com.au • www.foamular.com.au

NSW • QLD • VIC • WA • TAS • NZ