

FOAMULAR® INSULATION MAY BE THE PERFECT CHOICE



For decades, countless building designers and engineers have found FOAMULAR® extruded polystyrene insulation to be the perfect choice for a myriad of applications. FOAMULAR® insulation has a long term stable thermal resistance of R-5 per inch, measured after real time aging. It has a high resistance to moisture because it is closed cell and composed of hydrophobic polystyrene polymer, achieving its resistance to water without relying on facers. FOAMULAR® insulation has a wide range of compressive strengths and it enables sustainable building design concepts.

Choose FOAMULAR® insulation for your current and future projects.

FOOTNOTES

1. CAN-ULC-S770-03. Standard Test Method for Determination of Long-Term Thermal Resistance of Closed Cell Thermal Insulating Foams; Underwriters Laboratories of Canada, 7 Underwriters Road Toronto ON M1R 3B4
2. Testing LTTR, Testing Reveals the LTTR Method May be Over-Reporting Results, by Mark S. Graham; Professional Roofing, January 2006. National Roofing Contractors Association, 10255 W. Higgins Road Suite 600, Rosemont, IL 60018-5607
3. ASTM C 578-06. Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation; ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959
4. ASHRAE 90.1: "Energy Standard for Buildings Except Low-Rise Residential Buildings"; American Society of Heating, Refrigerating and Air-Conditioning Engineers, 1791 Tullie Circle, N.E. Atlanta, GA 30329
5. Underwriters Laboratories Roof Deck Construction #457, tested in accordance with UL Standard 1256.
6. FOAMULAR® Roofing and Waterproofing Manual, Owens Corning Publication No. 23149-A
7. Design Guide for Frost-Protected Shallow Foundations: NAHB Research Center, Upper Marlboro, MD; June 1994
8. Standard Specification for Extruded Foam Insulation Board (Polystyrene); AASHTO Designation: M230; American Association of State Highway and Transportation Officials
9. "FOAMULAR® Extruded Polystyrene Insulation Recycled After 17 Years on the Job at DFW Airport," Owens Corning Publication No. 59400
10. LEED-NC for New Construction, Version 2.2, U.S. Green Building Council, 1015 18th Street NW, Suite 508, Washington, D.C. 20036
11. Metal roof insulation case study, "Pink FOAMULAR® Insulation Holds its Value," Owens Corning Publication No. 10004083

FOAMULAR® EXTRUDED POLYSTYRENE INSULATION

Product Selection Guide

Construction Application	FOAMULAR® Product	SCS	GG	ASTM C578 Type	
GENERAL PURPOSE	150	+		X	Slab edge, foundation, under light slab, steel stud sheathing, masonry cavity wall, concrete tilt-wall, etc
	250	+		IV	
WALL					
Sheathing	Insulating Sheathing	+		X	Laminated film on both sides for added strength
	ProPink®	+		X	Reinforced laminated film on both sides for extra added strength
Masonry Cavity Wall	CW15	+		X	15 and 25 psi, 16" wide, fits between wall ties
	CW25	+		IV	
	High-R CW Plus	+		IV	25 psi, 16" wide, fits between wall ties. Higher R per in
Z-Furring	InsulPink Z®	+		X	Fits between Z-furring on inside surface of unit masonry or concrete walls
Insulated Concrete Sandwich Panels	PinkCore®	+		IV	Connector ties also available as part of structural wall system
ROOF					
Low Slope Commercial Roofing, Architectural Metal Roofing	ThermaPink® 18	+		X	18, 25, 40 psi, used in a variety of roofing systems over a variety of deck types
	ThermaPink® 25	+		IV	
	ThermaPink® 40	+		VI	
Recover Roofing	DuraPink®	+		IV	Used over existing membrane and under new mechanically attached single-ply
	DuraPink® Plus	+		IV	Fabric facer to separate XPS from new PVC membrane
PRMA, Plaza Deck, Waterproofing	404	+		VI	Bottom side drainage channels on 4 edges for PRMA
	604	+		VII	
	404RB	+		VI	Bottom side drainage channels and top side ribbed surface for use under pavers in PRMA
	604RB	+		VII	
	600	+		V	High load, vehicular traffic
	1000	+		V	Higher load, vehicular traffic
UNDER SLAB					
Load Bearing, High Strength, Under Industrial Slabs	400	+		VI	40, 60, 100 psi compressive strength. Engineer to match FOAMULAR® compressive strength needed to load on slab and slab design. Ranges from light pedestrian to heavy equipment and storage.
	600	+		VII	
	1000	+		V	
Under Slab, Low Temperature Storage	LT30	+		IV	30 psi. Light to medium loads
	LT40	+		VI	40 psi. Heavier loads
FOUNDATION					
Foundation	Insul-Drain®	+		IV	Filtration fabric faced with drainage channels in foam



OWENS CORNING FOAM INSULATION, LLC
 ONE OWENS CORNING PARKWAY
 TOLEDO, OHIO 43659
1-800-GET-PINK™
www.owenscorning.com

INNOVATIONS FOR LIVING®

Pub. No. 10010242-A Printed in U.S.A. May 2009. THE PINK PANTHER™ & © 1964-2009 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2009 Owens Corning.



The GREENGUARD INDOOR AIR QUALITY CERTIFIED Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute. LEED is a registered trademark of U.S. Green Building Council.